









Expansions, bus modules, Ethernet gateways

http://catalog.moeller.net

Moeller HPL0211-2007/2008

easy2... , easy6... , MFD-...



	Description	Inputs		Outputs		Supply voltage	For use with	Part no. Article no.	Price see price list	Std. pack	
		Digital	Relay 10 A (UL)	Transistor							
I/O expansions											
		12	6			100/240 V AC	easy700 easy800 EC4P MFD-CP8..	EASY618-AC-RE 212314		1 off	
		12	6			24 V DC		EASY618-DC-RE 232112			
		12		8		24 V DC		EASY620-DC-TE 212313			
			2			EASY202-RE¹⁾ 232186					
							easy700 easy800 EC4P MFD-CP8..	EASY200-EASY 212315		1 off	
Coupling module											
		For the connection of remote I/O modules up to 30 m.									
Expansion units for networking											
	AS-interface	AS-Interface connection Slave 4 inputs, 4 outputs, 4 parameter bits Addresses available: 0 to 31					easy700 easy800 EC4P MFD-CP8..	EASY205-ASI 221598		1 off	
	PROFIBUS-DP slave	PROFIBUS DP slave Addresses available: 1 to 126						EASY204-DP 212316			
	Fieldbus connection to CANopen	CANopen interface Addresses available: 1 to 127						EASY221-CO 233539			
	Fieldbus connection to DeviceNet	DeviceNet interface Addresses available: 0 to 63						EASY222-DN 233540			
Ethernet gateway											
	Protocols:ARP AutoIPDHCP HTTPICMP SNMPTCP TelnetTFTPUDP	Serial interface easy to Ethernet					easy500 easy700 easy800 MFD-CP8..	EASY209-SE 101520		1 off	
Power supply unit/communication modules											
	24 V DC						easy500 easy700	MFD-CP4-500 274094		1 off	
	24 V DC						easy800 MFD-CP8..	MFD-CP4-800 274095			
	100/240 V AC						easy500 easy700	MFD-AC-CP4-500 286823			
	100/240 V AC						easy800 MFD-CP8..	MFD-AC-CP4-800 286824			

Notes

¹⁾ Not for use in combination with EASY719-DA-... basic device

easy Control

