




Description		Part no. Article no.	Price see price list	Std. pack
Display/operating unit				
Graphics display: 132 × 64 pixels with switchable backlight Customized laser inscription, MFD-Combination-* possible → page 4/48 Switched Status-LED IP65, removable titanium front frame				
	With keypad and Moeller logotype NEMA 4x in connection with MFD-XM-80 protective membrane → Accessories	MFD-80-B 265251		1 off
	With keypad, without Moeller logotype NEMA 4x in connection with MFD-XM-80 protective membrane → Accessories	MFD-80-B-X 284905		
	Without keypad, with Moeller logotype NEMA 4x	MFD-80 265250		
	Without keypad, without Moeller logotype NEMA 4x	MFD-80-X 284904		
Power supply unit/CPU module				
Expandable with MFD-80-... and I/O module, easy expansions can be connected Serial interface IP20, springloaded terminals				
	100/240 V AC without easy-NET	MFD-AC-CP8-ME 274091		1 off
	100/240 V AC with easy-Net	MFD-AC-CP8-NT 274092		
	24 V DC without easy-NET	MFD-CP8-ME 267164		
	24 V DC with easy-NET	MFD-CP8-NT 265253		
Power supply unit/communication modules				
Serial interface, detachachable display for easy/MFD Intgrated connection cable (5 m, can be cut to length)				
	24 V DC easy500 easy700	MFD-CP4-500 274094		1 off
	24 V DC easy800 MFD-CP8..	MFD-CP4-800 274095		
	100/240 V AC easy500 easy700	MFD-AC-CP4-500 286823		
	100/240 V AC easy800 MFD-CP8..	MFD-AC-CP4-800 286824		