














		Description	Part no. Article no.	Price see price list	Std. pack	
AS-Interface connection for RMQ-Titan						
	For flush mounting panel (RMQ-Titan)	AS-Interface slave Adapter element for RMQ-Titan AS-Interface information: 2 input bits, 1 output bit Module enclosure to snap onto the contact and LED elements: – inputs for 2 contact sets: M22-K01 (N/C), M22-K10 (N/O) – Output for 1 LED element: M22-LED-... Including AS-Interface connector as insulation piercing terminal	M22-ASI 231269		1 off	
	For base fixing (RMQ-Titan)	Adapter element for RMQ-Titan AS-Interface information: 2 input bits, 1 output bit – Inputs for 2 contacts – Output for 1 LED element: M22-LED-...	M22-ASI-C 231271			
	For surface mounting enclosures (RMQ-Titan)	External connections: 4 inputs/4 outputs (for RMQ contact blocks and lamp socket elements) Surface mounting enclosures RMQ-Titan: M22-I3, M22-I4, M22-I6	RMQ-M1C-ASI 032314			
	For surface mounting enclosure (RMQ16)	External connections: 4 inputs/4 outputs (for RMQ contact blocks and lamp socket elements) Surface mounting enclosure, flush mounting plate RMQ16: I8, E8, E8-SW	RMQ-M2C-ASI 032315			
Emergency-Stop connections for AS-Interface – for safety monitor						
	For front fixing	AS-Interface slave Adapter element for RMQ-Titan AS-Interface information: 1 dual-channel input, 1 output Module enclosure to snap onto the contact and LED elements: Inputs for 2 contact elements: M22-K01 (N/C) – Output for 1 LED element: M22-LED-... Including AS-Interface connector as insulation piercing terminal	M22-ASI-S 231270		1 off	
	For base fixing	AS-Interface slave Adapter element for RMQ-Titan or FAK AS-Interface information: 1 dual-channel input, 1 output For the following RMQ-Titan contact blocks and LED's: - Inputs for 2 contact blocks M22-K01 or M22-KC01 (N/C) – Output for 1 LED element: M22-LED-...	M22-ASI-CS 231272		1 off	
		<ul style="list-style-type: none"> • M22-I2 and M22-I2Y surface mounting enclosures • M22-PVL emergency-off pushbutton and ON-OFF pushbutton; ON illuminated • 1 × M22-ASI-CS and 1 × M22-ASI-C • 1 × M12A connector • Addressing M22-PVL → 0; ON-OFF 1 A 	M22-I1/2-M1-ASI 107405		1 off	
		Lifespan to EN 60064 at t_0 = +25 °C t_{mean} (AC) h	Colour	Part no. Article no.	Price see price list	Std. pack
BA 9s filament bulbs for compact indicator lights						
High-grade versions from selected manufacturers						
	110 – 130 V/2.4 W	2000	–	A22-GL130 261361	100 off	
	24 V/2.0 W	5000	–	A22-GL24 261360	100 off	
BA 9s single-chip LEDs for compact indicator lights						
For AC and DC (positive pole connected to X1), protected against polarity reversal, built-in suppressor circuit up to 1500 V						
	18 ... 30 V AC/DC, 15 mA	100000	 white  Red  Green  Yellow	A22-LED-W 261362 A22-LED-R 261364 A22-LED-G 261363 A22-LED-Y 261365	10 off	