

Rated operational voltage	Rated operational current	Power consumption	Lifespan to EN 60064 at $t_a = +25\text{ °C}$	Colour	Part no. Article no.	Price see price list	Std. pack
$U_e$	$I_e$	$P_{max.}$	$t_{mean}$ (AC)				
V	mA	W	h				


## LED elements with Cage Clamp

→Engineering

Cage Clamp is a registered trademark of Wago Kontakttechnik GmbH/Minden, Germany




## Front fixing



12 ... 30 V AC/DC	8 – 15	0.26 W at 24 V	100000		M22-CLED-W 216569	20 off
					M22-CLED-R 216570	
					M22-CLED-G 216571	
					M22-CLED-B 218061	
85 ... 264 V AC, 50/60 Hz	5 – 15	0.33			M22-CLED230-W 216575	
					M22-CLED230-R 216576	
					M22-CLED230-G 216577	
					M22-CLED230-B 218063	

## Base fixing



12 ... 30 V AC/DC	8 – 15	0.26 W at 24 V	100000		M22-CLEDC-W 216572	20 off
					M22-CLEDC-R 216573	
					M22-CLEDC-G 216574	
					M22-CLEDC-B 218062	
85 ... 264 V AC, 50/60 Hz	5 – 15	0.33			M22-CLEDC230-W 216578	20 off
					M22-CLEDC230-R 216579	
					M22-CLEDC230-G 216580	
					M22-CLEDC230-B 218064	

## Notes

For pushbutton actuators, indicator lights, illuminated pushbuttons and illuminated selector switch actuators, the following applies:

M22...-R only in combination with M22-LED...-R  
M22...-G only in combination with M22-LED...-G  
M22...-W only in combination with M22-LED...-W  
M22...-Y only in combination with M22-LED...-Y  
M22...-B in combination with M22-LED...-W or M22-LED...-B

