








For use with	Col-our	Part no. Article no.	Price see price list	Std. pack	Notes
Built-in 2.0 A/A USB socket with connection cable					
IP65 with closed cover IP20 with plug connected					
	Front mounting Prefabricated cable with permanently connected USB 2.0 Type A plug	–	M22-USB-SA 107412	1 off	
Built-in RJ45 socket					
IP65 with closed cover IP20 with plug connected					
	Front mounting RJ45, 8/8	–	M22-RJ45-SA 107413	1 off	
Blade terminal to DIN 46244					
For connection of insulated ferrules for: main cables up to 25 A, 1 × 6.3 mm (DIN 46245) control circuit cables up to 6 A, 2 × 2.8 mm (DIN 46247)					
	DILEM, DILM17 – DILM1000 DILE... DILET... M22-K...	–	BT483 059904	100 off	Use insulated ferrules to DIN 46245.
Push-buttons					
For enclosed overload relays Mounting diameter: 22.3 mm					
	ZW7... ZB12 ZB32 ZB65 ZB150	–	M22-DZ-B 254833	10 off	Blue button plate
		–	M22-DZ-B-GB14 254834	10 off	Blue button plate: RESET
		–	M22-DZ-X 254835	10 off	Without button plate, button plate must be added
	M22-DZ-X M22(S)-D-X M22(S)-DR-X M22-DG-X	●	M22-XD-R 216423	10 off	Red legend plate
		◎	M22-XD-R-X0 218153	10 off	Button plate, red with white circle
		●	M22-XD-R-GB0 218194	10 off	Red legend plate STOP
Bulb extractor					
Compact indicating lamp M22-LC(H)...					
	A22-GL... A22-LED...	–	M22-LG 216403	5 off	
Notching tool					
Punching tool to produce the cutout for the anti-rotation lug to IEC/EN 60947-5-1 St 37 sheet steel, max. 3 mm thick VA high-grade steel max. 1.5 mm thick,					
		–	BA/C-NZ-22 028144	1 off	Price cannot be discounted
ATEX (Only in conjunction with M22-COMBINATION-*)					
For use in accordance with the ATEX directive in dust-laden areas, Zone 22, Category 3 → Engineering					
		–	M22-ATEX 104380	1 off	
Customer specific complete devices					
→ Engineering					
		–	M22-COMBINATION-* 228298	1 off	

