






















Type	Lifespan to EN 60064 at $t_a = +25^\circ\text{C}$ $t_{\text{mean}}(\text{AC})$ h	Colour	Part no. Article no.	Price see price list	Std. pack
Filament bulbs W 2 × 4.6 d					
	6 V/1.0 W	10000	–	WBGL6 090223	50 off
	12 V/1.0 W	15000	–	WBGL12 089968	50 off
	24 – 28 V/1.0 W	7000	–	WBGL24 089247	100 off
Multiple LEDs W 2 × 4.6 d					
For AC/DC 	6 V/45 mA	60000		WBLED-GE6 055711	10 off
				WBLED-GN6 055712	
				WBLED-RT6 055713	
	12 V/24 mA			WBLED-GE12 055714	
				WBLED-GN12 055715	
				WBLED-RT12 055716	
Single-chip LED W 2 × 4.6 d					
Positive pole to X1 Integral suppressor circuit up to 1000 V					
	18 – 30 V DC/7 – 12.5 mA	100000		LEDWB-Y 208724	10 off
				LEDWB-G 208725	
				LEDWB-R 208726	
				LEDWB-W 208728	
				LEDWB-B 208727	
Combination box spanner					
For lock nuts, with bulb extractor					
	–	–	–	R16-MS 090297	10 off
Insulated ferrule					
For 2.8 × 0.8 mm fast-on connectors, can be push-fitted from the front U _e > 50 V AC, U _e > 120 V DC					
	–	–	–	ISH2,8 090267	100 off
Fast-on connector					
2.8 × 0.8 mm for conductor cross-sections 0.5 – 1 mm ²					
	–	–	–	LT306.022.3 058863	100 off
Blanking plugs, IP65					
Degree of protection IP65 For blanking off reserve locations					
	For grid spacing 18 × 18 mm	–		Q18BS 037985	10 off
	For grid spacing 25 × 25 mm	–		Q25BS 036976	10 off
Anti-rotation feature					
Guard ring as anti-rotation feature for all RMQ16-actuators					
	–	–	–	VS 046301	50 off

