







	Colour		Part no. Article no.	Price see price list	Std. pack
Surface mounting enclosure, IP65¹⁾					
For conventional wiring or for mounting ILP1 circuit-boards with plastic cover fixing screws Enclosure base: black (RAL 9005) 8 mounting locations Knockout cable entries Floor: 4 × M20 Sides: 7 × M20					
	●	RAL 7035	I8 046299		2 off
	<hr/>				
Flush mounting plate, IP65¹⁾					
For conventional wiring or for mounting ELP 1 circuit-board 8 mounting locations					
	●	RAL 7035	E8 054423		1 off
	●	RAL 9005	E8-SW 065212		1 off
Customized complete units					
Ordering via FO315. (*) = customer identification or stock no. as required; max. 10 characters. Extra charge for small quantities ≤ 9 off + 50%					
	—		M16-COMBINATION-* 232189		1 off
Blanking plates, IP65					
For blanking off reserve locations in surface mounting enclosures or flush mounting panels, grid dimensions 25 × 37.5 mm					
	●	RAL 9005	Q25AS 036602		10 off
	●	RAL 7035	Q25AGR 048641		
	●		Q25AGE 048640		
Label mounts for insert plates²⁾					
For additional labelling of locations in surface mounting enclosures or flush mounting panels, grid dimensions 25 × 37.5 mm					
	●	RAL 9005	Q25TS-X 036601		20 off
	●	RAL 7035	Q25TGR-X 063257		
	●		Q25TGE-X 063258		

Notes

- ¹⁾ Unused locations must be closed off with blanking plates.
Each used mounting location must be fitted with a label mount.
- ²⁾ Suitable insert plates → 2/54