

	Function:	Button plate	Explanation	Front ring: titanium Part no. Article no.	Std. pack	Front ring: black Part no. Article no.	Std. pack
	= spring-return = stay-put						
Selector switch actuators, IP66							
ATEX → Engineering Front ring gold-plated, → page 2/37							
2 positions							
With rotary head							
	40°			M22-W 216853	5 off	M22S-W 216854	5 off
	60°			M22-WR 216855		M22S-WR 216856	
	60°			M22-WR-X92 216857		M22S-WR-X92 216858	
	60°		AUTO HAND	M22-WR-X91 216859		M22S-WR-X91 216860	
	60°	–	With inscription to order via Labeleditor, → Engineering	M22-WR-* 226836		M22S-WR-* 226837	
With thumb-grip							
	40°	–		M22-WK 216865	5 off	M22S-WK 216866	5 off
	60°	–		M22-WRK 216867	10 off	M22S-WRK 216869	10 off
	60°	–		M22-WRK-GVP 216868	50 off		off
With thumb-grip, V position							
	60°	–		M22-WKV 216874	5 off	M22S-WKV 216875	5 off
3 positions							
With rotary head							
	40° 40°			M22-W3 216861	5 off	M22S-W3 216862	5 off
	60° 60°			M22-WR3 216863		M22S-WR3 216864	
	60° 60°		AUTO 0 HAND	M22-WR3-X94 226838		M22S-WR3-X94 226839	
	60° 60°	–	With inscription to order via Labeleditor, → Engineering	M22-WR3-* 226840		M22S-WR3-* 226841	
With thumb-grip							
	40° 40°	–		M22-WK3 216870	5 off	M22S-WK3 216871	5 off
	60° 60°	–		M22-WRK3 216872		M22S-WRK3 216873	
		–		M22-WRK3-* ¹⁾ 217436		M22S-WRK3-* ¹⁾ 217437	
4 positions							
Not suitable for coding adapters. Use M22-A4 fixing adapter, → page 2/22 Labels → page 2/17							
With rotary head							
	45°			M22-WR4 279419	5 off	M22S-WR4 279430	5 off
With thumb-grip							
	45°			M22-WRK4 279431	5 off	M22S-WRK4 279432	5 off

Notes

- ¹⁾ Example: M22-WRK3-*
 * = 1: 60° 40°
 * = 2: 40° 60°

