















		Lifespan to EN 60064 at $t_a = +25\text{ °C}$ $t_{\text{mean}} \text{ (AC)}$ h	Rated operational voltage U_e V	Colour	Part no. Article no.	Price see price list	Std. pack
Accessories							
Stand with spacer							
	100 mm, black plastic	–	–	–	SL-F100 205345		1 off
	100 mm, metal	–	–	–	SL-F100M 265359		
	250 mm, black plastic	–	–	–	SL-F250 205346		
	250 mm, metal	–	–	–	SL-F250M 268925		
	400 mm, metal	–	–	–	SL-F400 215275		
	800 mm, metal	–	–	–	SL-F800 215276		
Fixing bracket 90° for wall mounting							
	Metal	–	–	–	SL-FW 205347		1 off
Filament bulb BA 15d, 5 ... 7 W							
		2000	24 V	–	SL-L24 205348		1 off
		5000	110 ... 130 V	–	SL-L130 205349		1 off
		5000	200 ... 260 V	–	SL-L230 205350		1 off
Multiple LED BA 15d, integral suppressor circuit up to 1500 V							
		100000	18 ... 30 V AC/DC 13 ... 50 mA		SL-LED-W 215278		1 off
					SL-LED-R 215279		
					SL-LED-G 215280		
					SL-LED-Y 215281		
					SL-LED-B 215282		
					SL-LED230-W 285532		
		110 ... 230 V AC 9 ... 17 mA		SL-LED230-R 285533			
				SL-LED230-G 285534			
				SL-LED230-Y 285535			
				SL-LED230-B 285536			
Gasket set To increase the degree of protection to IP65 (not applicable to acoustic indicator) For 3 modules \triangle 4 off							
	–	–	–	–	SL-IP65 215277		1 off

