


























| | Locations | Contacts M = make, B = break ⊖ = Safety function by positive opening of con- tacts to IEC/EN 60947-5- 1 | Contact sequence | Colour of enclosure top | Front ring: titanium Part no. Article no. | Price see price list | Std. pack |
|---|-----------|--|------------------|--|---|-----------------------------|-----------|
| | Number | | | | | | |
| Pushbuttons, IP67, IP69K | | | | | | | |
| Actuator flush  | 1 | 1 N/O | 1 N/C ⊖ |   | RAL 7035 | M22-D-G-X1/KC11/I 216522 | 1 off |
| | 1 | 1 N/O | 1 N/C ⊖ |   | RAL 7035 | M22-D-R-X0/KC11/I 216521 | 1 off |
| Emergency-Stop button, IP66, IP69K | | | | | | | |
| Tamperproof according to ISO 13850/EN 418 Pull to release  | – | | 2 N/C ⊖ |   | RAL 1004 | M22-PV/KC02/IY 216524 | 1 off |
| | – | 1 N/O | 1 N/C ⊖ |   | RAL 1004 | M22-PV/KC11/IY 216525 | 1 off |
| Emergency-Stop key-release mushroom button, IP67, 69K | | | | | | | |
| With 1 key MS1 lock mechanism  | 1 | 1 M | 1 N/C ⊖ |   | RAL 1004 | M22-PVS/KC11/IY 216523 | 1 off |
| IP66, key-operated buttons | | | | | | | |
| Stay-put/spring return function and key withdrawability convertible using M22-XC-... coding adapters, → Engineering With 1 key 2 positions, stay-put MS1 lock mechanism  | 1 | 1 N/O | 1 N/C ⊖ |   | RAL 7035 | M22-WRS/KC11/I 216526 | 1 off |
| Two-way pushbutton stations, IP67, 69K | | | | | | | |
| Without indicator light  | 2 | 2 N/O | 2 N/C ⊖ |   | RAL 7035 | M22-I2-M1 216529 | 1 off |
| With indicator light, white LED element 85 – 264 V AC  | 2 | 2 N/O | 2 N/C ⊖ |   | RAL 7035 | M22-I3-M2 216533 | 1 off |
| 3-way push-button station, IP67, IP69K | | | | | | | |
|  | 3 | 3 N/O | 3 N/C ⊖ |   | RAL 7035 | M22-I3-M1 216532 | 1 off |
| Customized complete units | | | | | | | |
| To order use form F0315 → Electronic Catalogue: RMQ-Titan → Product profile → Product information (*) = freely selectable customer identification or stock no.; max. 10 characters | | | | | | M22-COMBINATION-* 228298 | 1 off |

