











	For use with	Contact sequen.	Part no. Article no.	Price see price list	Std. pack	Notes
<b>Links</b>						
	DILM7 – DILM72 DILA	–	<b>DILM32-XVB</b> 281227		50	For mechanically arranging contactors in combinations. Distance between contactors 0 mm
	DILM80 – DILM150	–	<b>DILM150-XVB</b> 281226		10 off	
<b>Mechanical interlocks</b>						
	DILM7 – DILM15 DILMP20 DILA	–	<b>DILM12-XMV</b> 281196		1 off	For two contactors with AC or DC operation arranged vertically or horizontally Distance between contactors 0 mm, including contactor connector Mechanical lifespan 2.5 x 10 <sup>6</sup> operations. Additional auxiliary contact module possible → 5/28.
	DILM17 – DILM32	–	<b>DILM32-XMV</b> 281197		1 off	
	DILM40 – DILM72	–	<b>DILM65-XMV</b> 281198			
	DILM80 – DILM170	–	<b>DILM150-XMV</b> 240081			
	DILM185, DILM225, DILM250, DILM300, DILM400, DILM500	–	<b>DILM500-XMV</b> 208289		1 off	For two contactors with the same or different magnet system which are horizontally or vertically mounted, mechanical lifespan 5 x 10 <sup>6</sup> operations, between mechanical interlock and contactor <b>no</b> auxiliary contact possible. Combination with adjacent sizes only (DIL3... -DIL4... or DILM(C)185... -DILM(C)500) Distance between contactors: DIL3M80-4AM145 10 mm DILM(C)185-M(C)500 15 mm
	DILM580, DILM650 DILM750, DILM820, DILM1000	–	<b>DILM820-XMV</b> 208288		1 off	For contactors with the same or different magnet system mounted horizontally or vertically, mechanical lifespan 5 x 10 <sup>6</sup> operations. <b>No</b> auxiliary contact possible between mechanical interlock and contactor. DILM820-XMV consists of interlock element and mounting plate.
<b>Set of spare parts for mechanical interlock</b>						
–	DILM80 – DILM170		<b>DILM150-XMVE</b> 107020		1 off	Content: ball for mechanical interlock incl. contactor connector.
<b>4th pole</b>						
Only for AC 1 load, up to two auxiliary contacts can be fitted; suitable for isolating non-earthed and poorly earthed neutral conductors.						
	DILM40		<b>NDIL0M</b> 062006		1 off	<i>I<sub>e</sub></i> AC-1 Open/Enclosed 35 A/30 A
	DILM40		<b>NDIL1M</b> 060243			<i>I<sub>e</sub></i> AC-1 Open/Enclosed 55 A/44 A
	DILM50 DILM65 DILM72		<b>NDIL2M</b> 060264			<i>I<sub>e</sub></i> AC-1 Open/Enclosed 75 A/60 A

Contactors DILM, DILH  
Contactor relays

