

	Rated current = rated uninterrupted current	Short-circuit protection max. fuse gL- characteristic	Part no. Article no.	Price see price list	Part no. Article no.	Price see price list	Std. pack
	$I_n = I_u$						
	A	A gL					
<b>Switch-disconnectors</b>							
3 pole							
Terminals standard, terminal screws as accessories							
	63	125	<b>PN1-63</b> 259140		<b>N1-63</b> 259143		1 off
	100	125	<b>PN1-100</b> 259141		<b>N1-100</b> 259144		
	125	125	<b>PN1-125</b> 259142		<b>N1-125</b> 259145		
	160	160	<b>PN1-160</b> 281235		<b>N1-160</b> 281236		
Terminal screws standard, terminals as accessories							
	160	250	<b>PN2-160</b> 266005		<b>N2-160</b> 266008		1 off
	200	250	<b>PN2-200</b> 266006		<b>N2-200</b> 266009		
	250	250	<b>PN2-250</b> 266007		<b>N2-250</b> 266010		
	400	630	<b>PN3-400</b> 266017		<b>N3-400</b> 266019		1 off
	630	630	<b>PN3-630</b> 266018		<b>N3-630</b> 266020		
	630	1600			<b>N4-630</b> 107273		1 off
	800	1600			<b>N4-800</b> 266025		
	1000	1600			<b>N4-1000</b> 266026		
	1250	1600			<b>N4-1250</b> 266027		
	1600	1600			<b>N4-1600</b> 266028		

**Notes**

Main switch characteristics including positive drive to IEC/EN 60204 and VDE 0113

Isolating characteristics to IEC/EN 60947-3 and VDE 0660

Protection against accidental contact according to IEC 100

With the switch-disconnector N additional voltage releases NZM...-XU, NZM...-XA and trip-indicating auxiliary contacts (HIA) can be used.

N2..., N3... and N4... can also be combined with the NZM...-XR... remote operator.

Notes for terminals → 10/47