

DILL...


Moeller HPL0211-2007/2008

<http://catalog.moeller.net>

Lighting contactors DILL

Rated operational current				Conventional free air thermal current $I_{th} = I_e$ AC-1 at 60 °C Open	Contact sequence	Part no. Article no.	Price see price list	Std. pack
AC-5a operation		AC-5b operation						
230 V	400 V	230 V	400 V					
$I_e$	$I_e$	$I_e$	$I_e$					
A	A	A	A					

**Lighting contactors DILL**



12	12	14	14	24		<b>DILL 12(230V50HZ)</b> 104402		1 off
12	12	14	14	24		<b>DILL 12(24V50HZ)</b> 104401		
12	12	14	14	24		<b>DILL 12(400V50HZ)</b> 104403		
18	18	21	21	35		<b>DILL 18(230V50HZ)</b> 104405		
18	18	21	21	35		<b>DILL 18(24V50HZ)</b> 104404		
18	18	21	21	35		<b>DILL 18(400V50HZ)</b> 104406		
20	20	27	27	40		<b>DILL 20(230V50HZ)</b> 104408		
20	20	27	27	40		<b>DILL 20(24V50HZ)</b> 104407		
20	20	27	27	40		<b>DILL 20(400V50HZ)</b> 104409		

