








			Colour	Part no. Article no.	Price see price list	Std. pack	Notes
Insulated enclosures for surface mounting							
For motor-protective circuit-breakers, 3- or 4-pole circuit-breakers							
	Degree of protection IP40 Cover with aperture dimensioned to accommodate front of breaker, comes with blanking strip	PKZ2/ZM-... +NHI + AGM + U or A or RE or RS PKZ24/ZM-... + NHI + AGM + U or A		CI19EA-PKZ2 026234		1 off	Built-in IEC/EN 60715 top-hat rail, separate terminals for PE(N)- and N
	Degree of protection IP54 For mounting of (R)H-PKZ2 door coupling handle	PKZ2/ZM-... + NHI + AGM + U or A + (R)H		CI19EB-PKZ2 028607			incl. cable entry 2 × PG 16/21/29
	Degree of protection IP54 For mounting of (R)H-PKZ2 door coupling handle	PKZ24/ZM-... + NHI + AGM + U or A + (R)H		CI19ED-PKZ24 005145			L-PKZ0 indicator light can be fitted
For 3-pole compact starters, high-capacity compact starters, combination circuit-breakers (Kombi)							
	Degree of protection IP40 Cover with aperture dimensioned to accommodate front of breaker, comes with blanking strip	PKZ2/ZM-.../S(E1A) + NHI + AGM + RE or RS or U or A		CI23EA-PKZ2 087936		1 off	Complete with L3/5-CI23 mounting plate
	Degree of protection IP54 For mounting of (R)H-PKZ2 door coupling handle	PKZ2/ZM-.../S + NHI + AGM + U or A + (R)H		CI23EB-PKZ2 090309			Will accept compact starter or PKZ2/ZM-.../S high-capacity compact starter without clip plate
Insulated enclosures for flush mounting							
For motor-protective circuit-breakers, 3- or 4-pole circuit-breakers							
	Degree of protection IP41 Grey front plate with retaining frame Integral PE(N) terminal	PKZ2/ZM-... + NHI + AGM PKZ2/ZM-... + U or A PKZ24/ZM-... + NHI + AGM PKZ2/ZM-... +U or A (undervoltage or shunt release) PKZ24/ZM-...		E-PKZ2 003218		1 off	For mounting in side plate or door. Vertical mounting position. L-PKZ0 indicator light can be fitted
	Degree of protection IP54 (R)H-PKZ2 door coupling handle also required as standard	PKZ2/ZM-... + NHI + AGM PKZ2/ZM-... + U or A PKZ24/ZM-... + NHI + AGM PKZ2/ZM-... +U or A (undervoltage or shunt release) PKZ24/ZM-...		E54-PKZ2 033939			
Neutral terminal							
For connection of a 5th conductor							
		E-PKZ2 E54-PKZ2		N-PKZ2 003219		1 off	
Door coupling handles							
Degree of protection IP65							
	For use as main switch to IEC/EN 60204		Black	PKZ2-XH 106127		1 off	Lockable in 0 or I position Suitable for 3 padlocks with 4 – 8 mm hasp thickness
	For use in MCC distribution boards with PKZ2 turned through 90°. For use as main switch according to EN 60204		Black	PKZ2-XH-MCC 106130			
	For use as a main switch with Emergency-Stop function, to EN 60204		Red-yellow	PKZ2-XRH 106128			
Plug-fit extension shaft for door coupling handle							
Can be extended as required for mounting depths from 171 - 300 mm							
				PKZ2-XAH 106129		1 off	

PKZ2 motor-protective circuit-breaker

