









| Description | Insulation resistance range Ω | Contact sequence | Supply voltage | Part no. Article no. | Price see price list | Std. pack |
|--|---|---|---------------------|-------------------------------|-------------------------|-----------|
| EMR-4R... insulation monitoring relays | | | | | | |
|  <ul style="list-style-type: none"> Monitors the insulation resistance in non-earthed DC supply systems Selector switch between open-circuit or closed-circuit principle With test and reset facilities Status indication via LEDs | 10 – 110 k Ω |  | 24 – 240 V AC/DC | EMR4-RDC-1-A 221792 | | 1 off |
|  <ul style="list-style-type: none"> Monitors the insulation resistance between non-earthed AC supply systems and protective conductor/earth Tripping function memory Insulation monitoring in 1- and 3-phase AC supply systems Test via local test button or remote test/operation Status indication via LEDs to VDE 0413 / Part 2 | 1 – 110 k Ω |  | 24 – 240 V AC/DC | EMR4-RAC-1-A 221793 | | |
| | Mounting width mm | | | Part no. Article no. | Price see price list | Std. pack |
| EMR4-PH... sealable shroud | | | | | | |
|  | 22.5 | | | EMR4-PH22 221795 | | 1 off |
|  | 45 | | | EMR4-PH45 221794 | | |
| | For use with | | | Part no. Article no. | Price see price list | Std. pack |
| Remote potentiometer, IP66 | | | | | | |
| 10 k Ω ; 0.5 W max. | | | | | | |
|  | | DILET...ETR4-70 | | M22-R10K 229491 | | 1 off |
| | | DILET...ETR4-70 | | M22S-R10K 232233 | | 1 off |
| Screw adapter | | | | | | |
| For screw fixing | | | | | | |
|  | | EWDILETS4-VS3ETR4 | | CS-TE 095853 | | 10 off |

