





http://catalog.moeller.net

Moeller HPL0211-2007/2008

Motor-protective circuit-breakers  
PKZM01, PKZM0, PKZM4

Cable entry	Hole diameter mm	External diameter of cable mm	Part no. Article no.	Price see price list	Std. pack	
<b>Metric cable glands to EN 50262</b>						
<ul style="list-style-type: none"> <li>• With lock nut and integral strain relief</li> <li>• IP68 up to 5 bar, halogen free</li> </ul>						
	M20	20.5	6 – 13	V-M20 206910	20 off	
	M25	25.5	9 – 17	V-M25 206911		
	M32	32.5	13 – 21	V-M32 206912		
	M32	32.5	18 – 25	V-M32G 226156		
<b>Metric diaphragm grommets</b>						
<ul style="list-style-type: none"> <li>• IP65</li> <li>• With integral push-through diaphragm</li> </ul>						
	M20	20.5	1 – 13	KT-M20 207602	100 off	
	M25	25.5	1 – 18	KT-M25 207603		
	M32	32.5	1 – 24	KT-M32 207604		
<b>Door coupling handle IP65</b>						
Can be used with PKZM0 and PKZM4						
	For use as main switch to IEC/EN 60204	Black		PKZ0-XH 106132	1 off	Plug-in extension shaft A-H-PKZ0 can be cut to desired length for mounting depths of 100 – 240 mm. Carrier with extension shaft included in delivery. With ON/OFF switch position and "+" (tripped), lockable. With 3 padlocks, 4 – 8 mm hasp. Prepared for locking in ON.
	For use as a main switch with Emergency-Stop function, to EN 60204	Red-yellow		PKZ0-XRH 106133		
	For use as a main switch to EN 60204 in MCC power distribution systems and with PKZM0 installed when rotated by 90°	Black		PKZ0-XH-MCC 106136		
	For use as a main switch with Emergency-Stop function to EN 60204 in MCC power distribution systems and with PKZM0 installed rotated by 90°	Red-yellow		PKZ0-XRH-MCC 106137		
<b>Terminal shroud</b>						
	For enhancement of the degree of protection of the PKZM4 to IP2x		PKZM4	HB-PKZ4 256581	1 off	

