






| Contacts  | Rated switching distance | Rated operating voltage | Style    | Housing            | Terminal connection | Fitting in metal           | Part no. Article no. | Price see price list       | Std. pack                 |
|---|--------------------------|-------------------------|----------|--------------------|---------------------|----------------------------|----------------------|----------------------------|---------------------------|
| N/O = normally open contact, C/O = changeover contact, P = programmable as N/C or N/O | $S_n$<br>mm              | $U_e$<br>V DC           | mm       |                    |                     |                            |                      |                            |                           |
| <b>DC version, pulse-switching (PNP)</b>  |                          |                         |          |                    |                     |                            |                      |                            |                           |
|      | S                        | 1.5                     | 10 – 30  | M8 × 1             | Metal               | 2 m connection cable       | Flush                | LSI-R8S-F1-LD<br>281962    | 1 off                     |
|   | S                        | 1.5                     |          |                    | Metal               | Plug-in connection M12 x 1 | Flush                | LSI-R8S-F1-PD<br>281963    |                           |
|   | S                        | 3                       |          |                    | Metal               | Plug-in connection M12 x 1 | Non-flush            | LSI-R8S-NF3-PD<br>281964   |                           |
|   | S                        | 2                       |          | M12 × 1            | Insulated material  | 2 m connection cable       | Flush                | LSI-R12P-F2-LD<br>281908   |                           |
|   | S                        | 4                       |          |                    | Insulated material  | 2 m connection cable       | Non-flush            | LSI-R12P-NF4-LD<br>281909  |                           |
|   | S                        | 2                       |          |                    | Metal               | 2 m connection cable       | Flush                | LSI-R12M-F2-LD<br>281904   |                           |
|   | S                        | 2                       |          |                    | Metal               | Plug-in connection M12 x 1 | Flush                | LSI-R12M-F2-PD<br>281905   |                           |
|   | S                        | 4                       |          |                    | Metal               | Plug-in connection M12 x 1 | Non-flush            | LSI-R12M-NF4-PD<br>281906  |                           |
|   | S                        | 5                       |          |                    | M18 × 1             | Insulated material         | 2 m connection cable | Flush                      |                           |
|   | S                        | 8                       |          | Insulated material |                     | 2 m connection cable       | Non-flush            | LSI-R18P-NF8-LD<br>281955  |                           |
|   | S                        | 5                       |          | Metal              |                     | 2 m connection cable       | Flush                | LSI-R18M-F5-LD<br>281950   |                           |
|   | S                        | 5                       |          | Metal              |                     | Plug-in connection M12 x 1 | Flush                | LSI-R18M-F5-PD<br>281951   |                           |
|   | S                        | 8                       |          | Metal              |                     | Plug-in connection M12 x 1 | Non-flush            | LSI-R18M-NF8-PD<br>281952  |                           |
|   | S                        | 10                      |          | M30 × 1.5          |                     | Insulated material         | 2 m connection cable | Flush                      |                           |
|   | S                        | 15                      |          |                    | Insulated material  | 2 m connection cable       | Non-flush            | LSI-R30P-NF15-LD<br>281961 |                           |
|   | S                        | 10                      |          |                    | Metal               | 2 m connection cable       | Flush                | LSI-R30M-F10-LD<br>281956  |                           |
|   | S                        | 10                      |          |                    | Metal               | Plug-in connection M12 x 1 | Flush                | LSI-R30M-F10-PD<br>281957  |                           |
|   | S                        | 15                      |          |                    | Metal               | Plug-in connection M12 x 1 | Non-flush            | LSI-R30M-NF15-PD<br>281958 |                           |
|    | W                        | 20                      | 10 – 65  |                    | 114 × 40 × 40       | Insulated material         | Screw terminal       | Flush                      | LSI-Q40P-F20-CD<br>281998 |
|   | W                        | 40                      | 10 – 65  | 114 × 40 × 40      | Insulated material  | Screw terminal             | Non-flush            | LSI-Q40P-NF40-CD<br>282002 |                           |
|    | S                        | 20                      | 10 – 30  | 65 × 40 × 40       | Insulated material  | Plug-in connection M12 x 1 | Flush                | LSI-Q40P-F20-PD<br>281999  |                           |
|   | S                        | 35                      | 10 – 30  | 65 × 40 × 40       | Insulated material  | Plug-in connection M12 x 1 | Non-flush            | LSI-Q40P-NF35-PD<br>282001 |                           |
| <b>AC voltage version 50/60 Hz V AC</b>   |                          |                         |          |                    |                     |                            |                      |                            |                           |
|    | S                        | 2                       | 20 – 250 | M12 × 1            | Insulated material  | 2 m connection cable       | Flush                | LSI-R12P-F2-LA<br>281907   |                           |
|   | S                        | 5                       |          | M18 × 1            | Insulated material  | 2 m connection cable       | Flush                | LSI-R18P-F5-LA<br>281953   |                           |
|   | S                        | 10                      |          | M30 × 1.5          | Insulated material  | 2 m connection cable       | Flush                | LSI-R30P-F10-LA<br>281959  |                           |
|    | P                        | 20                      | 20 – 250 | 114 × 40 × 40      | Insulated material  | Screw terminal             | Flush                | LSI-Q40P-F20-CA<br>281997  |                           |
|   | P                        | 35                      |          | 114 × 40 × 40      | Insulated material  | Screw terminal             | Non-flush            | LSI-Q40P-NF35-CA<br>282000 |                           |

