



Contacts	Rated switching distance S_n mm	Rated operating voltage U_e V DC	Style mm	Housing	Connection type	Part no. Article no.	Price see price list	Std. pack
N/O = normally open contact, C/O = changeover contact, P = programmable as N/C or N/O								

LSC Capacitive proximity switches

Rated operational current I_{emax} . 200 mA
Fitting in metal: flush

	N/O	3	10 – 30	M12 × 1	Metal	2 m connection cable		1 off
	N/O	5	10 – 65	M18 × 1				
	C	10	10 – 65	M30 × 1.5				
	N/O	5	10 – 30	32 × 20 × 8	Insulated material	Screw terminal		
	C	20	10 – 65	114 × 40 × 40				

Operating range	Style	Housing	Terminal connection	Part no. Article no.	Price see price list	Std. pack
S_d	mm	mm				

LSO Optical proximity switches

Rated operating voltage U_e 10 – 30 V DC
Rated operational current I_{emax} . 150 mA
Output function M/B, programmable

Reflected-light beam



	300	M18 × 1	Insulated material	2 m connection cable	LSO-R18P-S300-LD 281987	1 off
	300	M18 × 1	Insulated material	Plug-in connection M12 x 1	LSO-R18P-S300-PD 281988	
	300	M18 × 1	Metal	2 m connection cable	LSO-R18S-S300-LD 281991	
	300	M18 × 1	Metal	Plug-in connection M12 x 1	LSO-R18S-S300-PD 281992	
With background suppression	400	M30 × 1.5	Insulated material	2 m connection cable	LSO-R30P-S400-LD 281995	
	400	M30 × 1.5	Insulated material	Plug-in connection M12 x 1	LSO-R30P-S400-PD 281996	

Reflected-light barrier
For combination with light-barrier reflector R...-ATL

	2000	M18 × 1	Insulated material	2 m connection cable	LSO-R18P-B2000-LD 281985	1 off
	2000	M18 × 1	Insulated material	Plug-in connection M12 x 1	LSO-R18P-B2000-PD 281986	
	2000	M18 × 1	Metal	2 m connection cable	LSO-R18S-B2000-LD 281989	
	2000	M18 × 1	Metal	Plug-in connection M12 x 1	LSO-R18S-B2000-PD 281990	
With polarisation filter	6000	M30 × 1.5	Insulated material	2 m connection cable	LSO-R30P-B6000-LD 281993	
With polarisation filter	6000	M30 × 1.5	Insulated material	Plug-in connection M12 x 1	LSO-R30P-B6000-PD 281994	

