



					Part no. Article no.	Price see price list	Std. pack
Light-barrier reflectors							
For combination with reflected-light barrier							
		Diameter: 40 mm			LSO-XR40 281983		1 off
		Diameter: 75 mm			LSO-XR75 281984		1 off
Length	Style input side	Style output side	Rated operating voltage	LED display	Part no. Article no.	Price see price list	Std. pack
m			U_e V				
Accessories: Plug and coupling, M12, "A" coded							
3-pole	1	Coupling, angled	Plug, straight	10 – 30	●	LSI-X3M-CAPS1-D4Y 281967	1 off
	2		Cable end open	10 – 30	●	LSI-X3M-CA2-D4Y 281965	
	5		Cable end open	10 – 30	●	LSI-X3M-CA5-D4Y 281966	
	1	Coupling, straight	Plug, straight	≅ 250		LSI-X3M-CSPS1-A4N 281969	
	1.5			≅ 250		LSI-X3M-CSPS1,5-A4N 281968	
	2			≅ 250		LSI-X3M-CSPS2-A4N 281970	
	5			≅ 250		LSI-X3M-CSPS5-A4N 281971	
4-pole	1	Coupling, angled	Plug, straight	10 – 30	●	LSI-X4M-CAPS1-D4Y 281974	1 off
	1	Coupling, straight	Plug, straight	≅ 250		LSI-X4M-CSPS1-A4N 281976	
	1.5			≅ 250		LSI-X4M-CSPS1,5-A4N 281975	
	2	Coupling, angled	Cable end open	≅ 250		LSI-X4M-CA2-A4N 281972	
	2	Coupling, straight	Cable end open	≅ 250		LSI-X4M-CS2-A4N 281973	
	2	Coupling, straight	Plug, straight	≅ 250		LSI-X4M-CSPS2-A4N 281977	
	5			≅ 250		LSI-X4M-CSPS5-A4N 281978	
			Plug, angled	Free	≅ 250		
		Plug, straight		≅ 250		LSI-X4M-PSF-A4N 281980	
		Coupling, angled		≅ 250		LSI-X4P-CAF-A4N 281981	
		Coupling, straight		≅ 250		LSI-X4P-CSF-A4N 281982	

