

Dimensions	Enclosure depth: Dimensions from top 1. Mounting depth for mounting plate 2. Mounting depth for mounting rails, 7.5 mm height 3. 7.5 mm mounting depth with mounting rails	Features	Part no. Article no.	Price see price list	Std. pack
mm	mm				
CI-K basic enclosures					
<ul style="list-style-type: none"> Degree of protection IP65 (Exception: CI-K2-80-A), material glass-fibre reinforced polycarbonate Enclosure base RAL 9005, black/enclosure top RAL 7035, light grey Metric cable entry knockouts top, bottom and in the back plate Push-through cable membrane on CI-K1 and CI-K2 Hard metric knockouts for sizes CI-K1H and CI-K2H Hard metric knockouts from sizes CI-K3 to CI-K5 Two protective covers to protect the push-through cable membrane with CI-K1 and CI-K2 Control cable entry from CI-K2 Lamp indicator L- can be mounted in base knock-out M20/M25 					
		With mounting rail	CI-K4-125-TS 206886		1 off
		With mounting plate	CI-K4-125-M 206897		
		With mounting rail	CI-K4-160-TS 206890		
		With mounting plate	CI-K4-160-M 206898		
		With mounting rail (weight of fitted components max. 0.65 kg, with additional mounting plate 1.7 kg)	CI-K5-125-TS 206891		
		With mounting plate	CI-K5-125-M 206899		
		With mounting rail (component weight max. 0.65 kg, with additional mounting plate 1.7 kg)	CI-K5-160-TS 206892		
		With mounting plate	CI-K5-160-M 206900		
Customized cutouts and laser inscriptions					
<ul style="list-style-type: none"> Only with enclosure cover The necessary data (laser data, symbols, text and their respective positions) as well as the position of the cut-outs must be provided as a DXF file. 					
			CI-K1-COMBINATION-* 102060		1 off
			CI-K2-COMBINATION-* 102061		
			CI-K3-COMBINATION-* 102062		
			CI-K4-COMBINATION-* 102063		
			CI-K5-COMBINATION-* 102064		