

Dimensions	Enclosure depth: Dimensions from top 1. Mounting depth for mounting plate 2. Mounting depth for mounting rails, 7.5 mm height 3. Enclosure depth	Features	Part no. Article no.	Price see price list	Std. pack
mm	mm				
CI-K basic enclosures					
<ul style="list-style-type: none"> Degree of protection IP65 (Exception: CI-K2-80-A), material glass-fibre reinforced polycarbonate Enclosure base RAL 9005, black/enclosure top RAL 7035, light grey Metric cable entry knockouts top, bottom and in the back plate Push-through cable membrane on CI-K1 and CI-K2 Hard metric knockouts for sizes CI-K1H and CI-K2H Hard metric knockouts from sizes CI-K3 to CI-K5 Two protective covers to protect the push-through cable membrane with CI-K1 and CI-K2 Control cable entry from CI-K2 Lamp indicator L- can be mounted in base knock-out M20/M25 					
		With mounting rail	CI-K1-95-TS 206881		1 off
		With mounting rail	CI-K1H-95-TS 105853		
		With mounting rail	CI-K2-100-TS 206882		
		With mounting rail	CI-K2H-100-TS 229304		
		With mounting plate	CI-K2-100-M 206893		
		With mounting plate	CI-K2H-100-M 229306		
		With mounting rail	CI-K2-145-TS 206883		
		With mounting rail	CI-K2H-145-TS 229305		
		With mounting plate	CI-K2-145-M 206894		
		With mounting plate	CI-K2H-145-M 229307		
		With adapter plate Prepared for fitting a DILE contactor with ZE overload relay	CI-K2-145-AD 207632		
		With adapter plate Prepared for fitting a DILE contactor with ZE overload relay	CI-K2H-145-AD 229308		
		With mounting rail	CI-K3-125-TS 206884		
		With mounting plate	CI-K3-125-M 206895		
		With mounting rail	CI-K3-160-TS 206885		
		With mounting plate	CI-K3-160-M 206896		



Notes Number and size of cable entries → page 7/63